
Floor Scales



Stainless Steel Floor Scale

with Easy-to-Lift Platform



Designed for Easy Cleaning in Hygienic Applications

PFA569lift Floor Scale

The PFA569lift floor scale simplifies washdown in hygienic applications. Its easy-to-lift platform allows quick access to the interior of the scale for thorough cleaning. One person can lift the platform manually. Made entirely of stainless steel, the PFA569lift floor scale is durable enough to provide accurate, repeatable weighing while standing up to constant use in wet and corrosive environments. A versatile design allows installation in a pit or on top of the floor. Adjustable feet make it easy to level the scale on uneven floors or when moving the scale to a new location.



Safe Operation

Built-in gas springs control lifting/lowering speed so that the platform opens with minimal effort and closes gently. The springs are sealed for safe, failure-proof operation.



Accurate Weighing

Hermetically sealed, stainless steel load cells with rocker feet deliver accurate, repeatable weighing.



Hygienic Rocker Feet

The rocker feet are designed to minimize exposed threads, making them easy to clean in hygienic applications.

Lift Handle

Insert the lift handle to raise/lower the platform and remove it to provide a smooth weighing surface with no threaded holes.





Durable Platform

Structural reinforcements give the platform exceptional strength while providing open areas to allow thorough cleaning.



Easy to Install

Installation is easy. Just attach chains to the lifting lugs and use a forklift or crane to set the scale in place. Then level the scale.



Robust Construction

The tubular stainless steel frame is designed for minimum deflection at maximum loads.



Automatic Lockdown

Spring-loaded plungers automatically lock the platform in place when it is lowered to the weighing position.

Specifications

48x48 and 60x60 inches (1219x1219 and 1524x1524 mm)
1000 lb / 600 kg, 2500 lb / 1200 kg, and 5000 lb / 3000 kg
3¼ inches (95 mm)
Type 304 stainless steel; 1/4-inch deck plate
Four 350-ohm load cells; hermetically sealed stainless steel
Stainless steel rocker-foot assembly
Stainless steel IP69K
100% end loading
14°F to 104°F (-10°C to 40°C)
NTEP, Measurement Canada, OIML (Pending)
FM, CSA, Ex, ATEX
480 and 568 lb (218 and 258 kg)
25 feet (7.6 meters)
Most METTLER TOLEDO terminals

Options

- Ramps
- Free-standing columns
- Instrument mounting brackets
- Longer load cell cables
- Factory calibration
- Optional material: Type 316 stainless steel
- Optional finishes: Electropolishing, mechanical polishes, ALGRIP™
- Pit frames
- Pit liners
- Remote junction boxes

www.mt.com/floorscale

For more information

Mettler-Toledo, LLC 1900 Polaris Parkway Columbus, Ohio 43240 Tel. (800) 786-0038 (614) 438-4511 Fax (614) 438-4900

Specifications subject to change without notice. $\ensuremath{\textcircled{O}}$ 2012 Mettler-Toledo, LLC

03/2012 111-FS03529.0E

